

QUESTIONS & ANSWERS

Kill your exam at first Attempt



Cisco

400-351

CCIE Wireless

Question: 198

Which three security threats require the Cisco Adaptive WIPS service for mitigation? (Choose three.)

- A. on/off-channel rogue
- B. spectrum intelligence
- C. man-in-the-middle attack
- D. rogue switch-port tracing
- E. zero-day attack
- F. network reconnaissance

Answer: C,E,F

Question: 199

Which of the following are required components for Client MFP? (Choose two.)

- A. CCXv4
- B. CCXv5
- C. 802.11n
- D. WPA2 w/TKIP or AES-CCMP
- E. AnyConnect 3.0

Answer: B,D

Question: 200

_____ is classified as an 802.11i RSN with _____ as the mandatory encryption protocol.

- A. WEP, TKIP
- B. WPA2,TKIP
- C. WPA, AES
- D. WPA2, AES

Answer: D

Question: 201

A clause 15 radio uses _____ and supports data rates of _____ .

- A. FHSS or DSSS, 1 Mb/s up to 11 Mb/s
- B. DSSS, 1 Mb/s and 2 Mb/s
- C. FHSS, 1 Mb/s and 2 Mb/s
- D. DSSS, 1 Mb/s up to 11 Mb/s

Answer: B

Question: 202

Which statement about heat maps on Cisco WCS is true?

- A. They are predictive and rely only on the accuracy of the information that is provided with the map.
- B. They are based on real-time actual values if Cisco Compatible Extensions is enabled on the APs.
- C. They are predictive but can be converted to real values by using the Refresh from network button.
- D. They are based on real-time actual values because of fingerprinting.

Answer: A

Question: 203

You are designing a wireless network utilizing EAP-TLS. One design requirement is to provide per-user differentiated QoS using only one SSID. What is the best way to achieve this goal?

- A. using WMM override
- B. using Cisco Airespace VSAs
- C. using QoS Enhanced BSS
- D. using AP groups

Answer: B

Question: 204

What does the letter P in the designation of the AIR-CAP3502P AP indicate?

- A. The AP supports the new IEEE 802.11p (WAVE) wireless standard.
- B. The AP requires professional installation.
- C. The AP can be used in plenum applications.
- D. The AP is compatible with polarization type antennae.

Answer: B

Question: 205

You are converting your wireless infrastructure from a data-only design to a location services design. Which task do you need to complete?

- A. Disable the DSSS speeds for RFID compatibility.
- B. Use fewer APs to avoid RFID 3D imaging.
- C. Set APs to maximum power for RF fingerprinting.
- D. Locate APs at the edges of your coverage area for trilateration.

Answer: D

Question: 206

Which two security features are associated with a wireless network employing 802.11i configured as a Robust Security Network? (Choose two.)

- A. WEP
- B. AES-CCMP
- C. 802.11x
- D. IPsec
- E. TKIP
- F. 802.1x

Answer: B,F

Question: 207

Before conducting a passive RF site survey with a standalone AP, which two of these should be statically configured on the AP? (Choose two.)

- A. passive client
- B. channel assignment
- C. DTPC
- D. Tx power level
- E. channel scan defer priority

Answer: B,D

Question: 208

After interviewing a customer to understand wireless client requirements, you determine that 802.11b must be enabled to support legacy clients within a mixedmode environment. Which recommendation will have the greatest impact on mitigating the effects of 802.11b clients on the rest of the network?

- A. Restrict OFDM modulation from being used.
- B. Make 11 Mb/s the lowest mandatory rate.
- C. Enable a separate SSID for 802.11b clients.
- D. Enable a short preamble.

Answer: B

Question: 209

In a Cisco Unified Wireless Network environment, which two of these are required in order for clients to connect with MCS data rates? (Choose two.)

- A. EDCF
- B. client MFP
- C. multiple spatial streams
- D. AES-CCMP
- E. 40-MHz channels

Answer: A,D

Question: 210

The 802.11-2007 standard includes which two amendments to the original 802.11 standard? (Choose two.)

- A. 802.11c

- B. 802.11d**
- C. 802.11j**
- D. 802.11r**
- E. 802.11u**

Answer: B,C

