

QUESTIONS & ANSWERS

Kill your exam at first Attempt



Cisco

642-999

*Implementing Cisco Data Center Unified Computing (DCUCI)
v5.0*

- A. Realm
- B. LDAP Provider Group
- C. Authentication Domain
- D. Organization

Answer: B

QUESTION: 164
Refer to the exhibit.



An admin is configuring VLANs on a Cisco UCS B-Series vNIC. Which two statements about the traffic coming from the operating system with this configuration are true? (Choose two.)

- A. The VLAN must be configured with ID 832 within the operating system.
- B. No VLAN tag should be added in the operating system.
- C. If traffic comes in untagged on this vNIC, it is placed in VLAN 832.
- D. This configuration is not supported when hypervisors are used.
- E. The uplink ports of the fabric interconnect have the native VLAN set to ID 832.

Answer: B, C

QUESTION: 165
What are the default settings of the Cisco IMCCIMC NIC properties on a standalone Cisco UCS C-Series server?

- A. 'Shared LOM' NIC mode with 'Active-active' NIC redundancy and DHCP enabled
- B. 'Shared LOM' NIC mode with 'Active-standby' NIC redundancy and DHCP enabled
- C. 'Dedicated' NIC mode with 'Active-standby' NIC redundancy DHCP disabled
- D. 'Dedicated' NIC mode with 'None' NIC redundancy and DHCP enabled
- E. 'Cisco Card' NIC mode with 'Active-active' NIC redundancy and DHCP enabled

Answer: D

QUESTION: 166

Where do you configure the VLAN when provisioning new VLANs in VM-FEX?

- A. vCenter on the port group
- B. Cisco UCS Manager on the port profile
- C. Cisco UCS Manager on the service profile
- D. vCenter on the host

Answer: B

QUESTION: 167

With Cisco UCS Manager, in which location do you monitor the chassis discovery process?

- A. CMC
- B. FSM
- C. CDP
- D. DME

Answer: B

Reference:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/20/b_UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_0100011.html

QUESTION: 168

Which authentication provider requires a custom attribute?

- A. TACACS+
- B. RADIUS
- C. LDAP
- D. local authentication

Answer: A

Reference:

http://www.cisco.com/en/US/docs/unified_computing/ucs/sw/gui/config/guide/141/UCS_M_G_UI_Configuration_Guide_141_chapter7.html

QUESTION: 169

Which three statements about default settings for fabric interconnect uplink ports are true? (Choose three.)

- A. When a VLAN is configured, it is trunked on all uplinks.
- B. Specific VLANs are trunked on specific uplinks.
- C. UDLD is enabled.
- D. UDLD is disabled.
- E. Cisco Discovery Protocol is enabled.
- F. Cisco Discovery Protocol is disabled.
- G. They connect to the I/O modules.

Answer: A, D, E

QUESTION: 170

Which statement about high-availability clusters for Cisco UCS Fabric Interconnects is true?

- A. Peers in a cluster must connect to each other by using two 10-Gbps links.
- B. The cluster requires a minimum of two IP addresses.
- C. The management plane is active/standby.
- D. The data plane is active/standby.

Answer: C

Reference:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/20/b

[UCSM_GUI_Configuration_Guide_2_0/b_UCSM_GUI_Configuration_Guide_2_0_chapter_01_00.html](http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/1-0-2/b_GUI_Config_Guide/GUI_Config_Guide_chapter_01_00.html)

QUESTION: 171

Which two constructs allow for configuration of VLANs on specific uplink ports?
(Choose two.)

- A. LAN pin group
- B. adapter policies
- C. vNIC templates
- D. VLAN manager
- E. link profiles
- F. VLAN groups

Answer: A, C

Reference:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/1-0-2/b_GUI_Config_Guide/GUI_Config_Guide_chapter17.html

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/sw/gui/config/guide/1-0-2/b_GUI_Config_Guide/GUI_Config_Guide_chapter14.html

QUESTION: 172

Which two settings are required when utilizing Direct Path I/O? (Choose two.)

- A. CPU pinning
- B. full memory reservation
- C. Set port profile performance to "high".
- D. vCPU pinning
- E. VM queue modification
- F. adapter profile update
- G. Install DirectPath VIB on host.
- H. Enable VMQ with the "enable-netadaptervmq" cmdlet.

Answer: B, C

QUESTION: 173

Which item describes the failure scenario called a "split-brain" in the Cisco Unified

Computing System?

- A. failure of the Cisco Unified Computing System L1-L2 network
- B. failure of a Cisco Unified Computing System Chassis Management Controller
- C. failure of a Cisco Unified Computing System I/O module
- D. failure of a Cisco Unified Computing System Fabric Interconnect
- E. failure of a Cisco Unified Computing System Chassis Management Switch

Answer: A

For More exams visit <http://killexams.com> -



KILLEXAMS.COM

Kill your exam at First Attempt....Guaranteed!